

# BOMFORD Hawk <sup>Evo</sup>



The new Bomford Hawk "Evo" range of arm mowers provides the professional customer with an extensive choice of arm reaches, controls, tractor fitting and cutting head options that will ensure Bomford has the right arm mower to suit every application. The Hawk provides cutting reaches between 5.4 and 6.5 metres in either a conventional straight arm or with the increasingly popular 1 metre forward arm option for operator in-line vision. A 100 litre/min Hydraulic system comes standard while the forward arm models can upgrade to 125 litres/min or even a new Piston pump system can be offered for those customers demanding extra power and efficiency in cutting.

The Bomford Hawk "Evo" offers 4 types of arm control including the proven top of the range ICS (Intelligent Control System) that provides fully proportional fingertip control with programs tailored to suit the operator. Hawk joystick controls are equipped with large capacity fan controlled oil coolers to ensure all day long performance. The Pro-Trim 1200mm or 1500mm flail cutting head is the popular choice with proven features like the top drive hydraulic motor for reliable power transmission and compact dimensions, also the double spiral rotor shaft provides a strong mounting point for the 6 types of interchangeable flails depending on the type of vegetation and conditions. With our forward arm models a new 180 degree head turntable ensures a tight transport width. In addition to the Pro-Trim flail head, Bomford can offer Sheartrim cutterbar and Pro-Saw attachments to tackle brush and tree growth. Durable powder paint finish and new high visibility LED rear lights ensure your Bomford Hawk will be visible when working on the highways.



Pro-Trim flail head



Pro-Saw attachment



Sheartrim cutterbar



ICS Control

Hawk Specifications	Hawk 5.4 100 litre	Hawk 6.0 100 litre	Hawk 6.5 100 litre Telescopic	Hawk 5.4 Fwd 100 litre	Hawk 6.0 Fwd 100 litre
Reach in metres	5.4 (17'9")	6.0 (19'8")	6.5 (21'4")	5.4 (17'9")	6.0 (19'8")
Min Tractor Horse Power (PTO)	65hp	65hp	70hp	65hp	70hp
Min Tractor Weight	3000KG (6,600lb)	3250KG (7,165lb)	4000KG (8,818lb)	3250KG (7,165lb)	3800KG (8,378lb)
Weight Without Oil & Head	935KG (2061lb)	1085KG (2392lb)	1300KG (2866lb)	1260KG (2778lb)	1400KG (3086lb)
Oil Tank Capacity	180 Litres (48gal)	180 Litres (48gal)	180 Litres (48gal)	250 Litres (66gal)	250 Litres (66gal)
Weight With Oil, No Head	1100KG (2425lb)	1250KG (2756lb)	1500KG (3307lb)	1460KG (3219lb)	1600KG (3527lb)
System Capacity	59hp	59hp	59hp	59hp	59hp
Pump Flow Rate	104ltr (28gal/min)	104ltr (28gal/min)	104ltr (28gal/min)	104ltr (28gal/min)	104ltr (28gal/min)
Pump Gear Type	Gear / Gear	Gear / Gear	Gear / Gear	Gear / Gear	Gear / Gear
Pump Arrangement	Twin	Twin	Twin	Twin	Twin
Independent Hydraulics	Standard	Standard	Standard	Standard	Standard
Gearbox	Cast Iron 540rpm	Cast Iron 540rpm	Cast Iron 540rpm	Cast Iron 540rpm	Cast Iron 540rpm
Oil Cooler Standard on	LPH, EPP + ICS	LPH, EPP + ICS	LPH, EPP + ICS	LPH, EPP + ICS	LPH, EPP + ICS
Head angle rotation degrees	245	245	245	245	245
Telescopic 2 <sup>nd</sup> arm	N/A	N/A	0.9m (36")stroke	N/A	N/A
Forward Arm	No	No	No	Yes	Yes
Forward Arm Reach	N/A	N/A	N/A	1035mm (40")	1035mm (40")
Power Slew	Yes	Yes	Yes	Yes	Yes
Power Slew Angle	94 deg	94 deg	94 deg	94 deg	94 deg
Hydraulic Breakout	Standard	Standard	Standard	Standard	Standard
Arm Float - Manual Standard On	Cable	Cable	Cable	Cable	Cable
Arm Float - Electronic Standard On	LPH, EPP + ICS	LPH, EPP + ICS	LPH, EPP + ICS	LPH, EPP + ICS	LPH, EPP + ICS
Head Float - Manual Standard On	Cable	Cable	Cable	Cable	Cable
Head Float - Electric Standard On	LPH, EPP + ICS	LPH, EPP + ICS	LPH, EPP + ICS	LPH, EPP + ICS	LPH, EPP + ICS
<b>Arm Attachments Available</b>	<b>Hawk 5.4 100 litre</b>	<b>Hawk 6.0 100 litre</b>	<b>Hawk 6.5 100 litre Telescopic</b>	<b>Hawk 5.4M 100 litre</b>	<b>Hawk 6.0M 100 litre</b>
Variable Track Bracket ( VTB )	Optional	Optional	Optional	N/A	N/A
Sheartrim Cutterbar	Optional	Optional	Optional	Optional	Optional
Pro-Saw Sawhead	Optional	Optional	Optional	Optional	Optional
<b>Accessories</b>	<b>Hawk 5.4 100 litre</b>	<b>Hawk 6.0 100 litre</b>	<b>Hawk 6.5 100 litre Telescopic</b>	<b>Hawk 5.4M 100 litre</b>	<b>Hawk 6.0M 100 litre</b>
LED Road Lights	Standard	Standard	Standard	Standard	Standard
Debris Blower	Optional	Optional	Optional	Optional	Optional
Cab Guard Kit	Standard	Standard	Standard	Standard	Standard
3 Point Linkage Stabiliser	Standard	Standard	Standard	Standard	Standard
Axle Brackets	Optional	Optional	Optional	Optional	Optional
<b>Hydraulic Controls</b>	<b>Hawk 5.4 100 litre</b>	<b>Hawk 6.0 100 litre</b>	<b>Hawk 6.5 100 litre Telescopic</b>	<b>Hawk 5.4M 100 litre</b>	<b>Hawk 6.0M 100 litre</b>
Cable Control	Optional	Optional	Optional	Optional	Optional
Electric Proportional Control (EPP)	Optional	Optional	Optional	Optional	Optional
Intelligent Control System (ICS)	Optional	Optional	Optional	Optional	Optional
Low Pressure Hydraulics (LPH)	Optional	Optional	Optional	Optional	Optional
Cable Rotor Reverse (Standard On)	Cable + LPH	Cable + LPH	Cable + LPH	Cable + LPH	Cable + LPH
Electric Rotor Control (Standard On)	EPP + ICS	EPP + ICS	EPP + ICS	EPP + ICS	EPP + ICS
<b>Reach Specs in Metres</b>	<b>Hawk 5.4 100 litre</b>	<b>Hawk 6.0 100 litre</b>	<b>Hawk 6.5 100 litre Telescopic</b>	<b>Hawk 5.4M 100 litre</b>	<b>Hawk 6.0M 100 litre</b>
A	5.4 (17'9")	6.0 (19'8")	6.5 (21'4")	5.4 (17'9")	6.0 (19'8")
B	5.5 (18')	6.1 (20')	6.65 (21'8")	5.5 (18')	6.15 (20'1")
C	3.7 (12'5")	4.3 (14'1")	4.85 (15'9")	3.8 (12'5")	4.4 (14'5")
D	4.8 (15'7")	5.4 (17'7")	5.8 (19')	4.5 (14'8")	4.9 (16'1")
E	6.7 (22')	7.3 (23'11")	7.72 (25'5")	6.8 (22'3")	7.2 (23'6")
X	1.35 (4'5")	1.35 (4'5")	1.35 (4'5")	1.35 (4'5")	1.35 (4'5")
Y	1.0 (3'4")	1.0 (3'4")	1.0 (3'4")	1.0 (3'4")	1.0 (3'4")

YOUR DISTRIBUTOR

**Bomford Turner**  
**Station Road, Salford Priors**  
**Evesham**  
**Worcestershire WR11 8SW**  
**Tel: 01789 773383 Fax: 01789 773238**  
**Email: info@bomford-turner.com**

