

ISEKI

TXG237



The TXG237 benefits from a flat easy-access platform. Clear automotive style dashboard and controls, with switchable 4WD drive make the TXG237 very user friendly. Individual forward and reverse pedals give the operator precise control.

Its compact dimensions and powerful 23 hp diesel engine makes the TXG237 a multi-purpose grounds care tractor. Robust enough to take a front loader or back hoe and other implements via a Cat 1 3-point hitch including collectors and centre mounted mowing decks; this is a versatile machine for any application.



Optional loader and counterweight

Power: 16.8 kW (23hp)

Drive System: Hydrostatic

Special Features: Independent PTO, high ground clearance, includes auxillary hydraulic valve with two double acting spools, easily attached/detached mower deck

 **ISEKI**

www.iseki.co.uk



TXG237 Technical Data

Power	Engine: Type	Diesel, indirect injection, overhead valve
	Displacement	1123cc
	No of cylinders	3
	Power	16.8kW (23hp) at 2600rpm
	Fuel capacity	21 ltr (4.6gal)
Transmission	Type	Hydrostatic
	Gears forward/reverse	2/2
	Speed	0 -14.3km/h (8.8mph)
Brakes	Type	Mechanically actuated, sealed wet discs
Tyres	Front	18 x 8.50-8 Semi-ag or turf tyres
	Rear	26 x 12.0-12 Semi-ag or turf tyres
PTO	Engagement	Hydraulic
	Rear PTO at engine rpm	540 at 2532rpm
	Mid PTO at engine rpm	2000 at 2476rpm
Hydraulics	Steering	Hydrostatic (power)
	Main system	Transmission mounted gear pump with flow divider
	Max output at engine rpm	23.1 ltr/min (5.1gal/min) at 2500 rpm
	Three-point lift	Category 1
	Lift capacity	540kg (1190lbs) at ball end
	Dimensions	Height over steering wheel 1.29m (51")
	Height over ROPS	2.25m (88")
	Width	1.19m (47")
	Length	2.48m (97.6")
	Wheelbase	1.45m (57")
	Ground clearance	215mm (8.4")
	Weight with ROPS	665kg (1463lbs)
Mower Deck	1.22m (48") side and rear discharge	
	1.37m (54") side and rear discharge	
	1.5m (60") side discharge	
	1.37m (54") mulching	
Optional Equipment	550 litre low dump collector with 540 rpm blower and collector frame available.	



Optional A-frame front linkage and hydraulic outlet

ISEKI UK & Ireland

5, Foxtail Road, Ransomes Europark,
Ipswich, IP3 9RT, UK
Tel: 0044 (0) 1473 599266

www.iseki.co.uk

