

Compact

14.30 - 15.30 - 16,30

New



Offering you a wider choice



Hydr. folding roller with 5 horizontal roller sections and very low centre of gravity. All operations are controlled from the tractor. By virtue of the big overlap between each section an optimal rolling is achieved across the whole working width – even when turning and in uneven ground. The hydr. weight transfer allows weight to transfer from the middle section to the side sections achieving an even soil pressure over the entire working width. The **DUOFLEX-System** ensures that each roller section works independently.

- Heavy duty 10 mm profile frame
- Hydr. weight distribution
- Duoflex-system via accumulator
- Hydr. brakes
- Hydr. jack



Technical specifications:

Type (width)	14,30m	15,30m	16,30m
50cm Cambridge - weight/nos of rings	8400 kg/285	8675 kg/305	8880 kg/325
55cm Cambridge - weight/nos of rings	9750 kg/305	10065 kg/305	10380 kg/325
53cm Crosskill - weight/nos of rings	7620 kg/143	7700/153	7950 kg/163
60cm Crosskill - weight/nos of rings	9410 kg/143	10230 kg/153	9990 kg/163
HP required	Min. 190 HP	Min. 210 HP	Min. 230 HP
Transport width:	3 m	3 m	3 m
Wheels	600/50-22,5 TWIN 404	600/50-22,5 TWIN 404	600/50-22,5 TWIN 404
Hydraulic services	3 x D acting	3 x D acting	3 x D acting