

AW TRAILERS

Ultima



The Ultima range of Trailers from AW Engineering has an Ultra High Specification and the same High Quality Build as All AW Trailers.

They are Durable and Reliable Trailers designed to meet the needs of contractors and large scale farmers.

AW Engineering (Hereford) Ltd.
Stoney Street
Madley
Hereford
HR2 9NQ

Tel : 01981 251558
Fax : 01981 251568

Web : www.awtrailers.co.uk
Email : sales@awtrailers.co.uk



- New Commercial Parabolic Sprung Suspension
- 10 Stud High Speed Axles
- 420 x 180mm Brake giving Braking Efficiency of 40% with Hydraulic Brakes and 50% with Air Brakes
- 445/65R22.5 Kargo Radial Tyres fitted as standard (huge selection of flotations available)

- Hydraulic Load Sensing fitted as standard
- **High Speed Option.** When fitted with optional extras of air brakes with load sensing and ABS the 'Ultima' trailers are suitable for hauling at speeds of up to 40mph (when towed by an appropriate vehicle)



- Multi-Adjustable Height Positions
- 60mm Phosphor Bronze Bushes
- Chrome Pivots
- Multi-Leaf Drawbar Spring
- Heavy Duty Hitch Eye

- Commercial LED Full Road Lighting (Front, Side and Rear)
- Using Maintenance Free LED Lamps
- No Bulbs
- LED Beacon available



- Full Steel Mudguards
- Removable & Adjustable
- Complete with Mud Flaps

- Heavy Duty Hitch Eye welded on rear of Chassis



Standard body features include

- Large Capacity Body - no taper available if required
- 4mm thick sides, fully welded with wide side channels and rigid heavy duty RHS box section top and rear corner posts
- 5mm thick floor with additional floor supports
- Optional Contractor Hydraulic Tailboard available complete with Combination Equalizer / Check Valves



de :-
taper
)
ded
nd
er

Standard chassis features include :-

- Wide Chassis for greater stability
- Increased tipping angle
- Bulk head couplings on front of chassis

All 'Ultima' trailers have our Premium Paint Finish which includes :-

- Choice of colour (within standard tractor range)
- Trailer thoroughly degreased and then shotblasted prior to painting
- Painted with 2 Pack Primer and 2 Pack Top Coat to give hard wearing gloss finish

Full width Front Windows feature a Laser Cut Grill. (Standard on Potato & Root models.)



- Side to Side Roll-Over Sheet available.
- Comes complete with fold down access ladder attached to tailboard



	12 Tonne Ultima Monocoque		14 Tonne Ultima Monocoque		16 Tonne Ultima Monocoque	
Body length (internal)	5505mm	18'	6100mm	20'	6700mm	22'
Body width (internal)	2275mm	7' 6"	2275mm	7' 6"	2275mm	7' 6"
Body height (internal)	1270mm	4' 2"	1270mm	4' 2"	1270mm	4' 2"
Floor thickness	5mm		5mm		5mm	
Side thickness	4mm		4mm		4mm	
Cubic capacity	15.9m ³	565ft ³	17.6m ³	625ft ³	19.4m ³	688ft ³
Chassis	250 x 150 RHS		250 x 150 RHS		250 x 150 RHS	
Axle size	127mm diameter 10 stud		127mm diameter 10 stud		127mm diameter 10 stud	
Brake size	420 x 180mm		420 x 180mm		420 x 180mm	
Wheel track	2000mm	6' 7"	2000mm	6' 7"	2000mm	6' 7"
Tyre size	445/65R22.5 Kargo radial		445/65R22.5 Kargo radial		445/65R22.5 Kargo radial	
O/all length	7125mm	23' 3"	7730mm	25' 3"	8330mm	27' 4"
O/all width	2455mm	8' 1"	2455mm	8' 1"	2455mm	8' 1"
O/all height	2650mm	8' 8"	2650mm	8' 8"	2650mm	8' 8"
Max tipped height	6390mm	21'	6850mm	22' 6"	7410mm	24' 4"
Unladen weight	Approx 5.0 Tonne		Approx 5.3 Tonne		Approx 5.7 Tonne	

	12 Tonne Ultima Potato & Root		14 Tonne Ultima Potato & Root		16 Tonne Ultima Potato & Root	
Body length (internal)	6100mm	20'	6700mm	22'	6700mm	22'
Body width (internal)	2275mm	7' 6"	2275mm	7' 6"	2275mm	7' 6"
Body height (internal)	1070mm	3' 6"	1070mm	3' 6"	1270mm	4' 2"
Floor thickness	5mm		5mm		5mm	
Side thickness	4mm		4mm		4mm	
Cubic capacity	15m ³	525ft ³	16.3m ³	578ft ³	19.4m ³	688ft ³
Chassis	250 x 150 RHS		250 x 150 RHS		250 x 150 RHS	
Axle size	127mm diameter 10 stud		127mm diameter 10 stud		127mm diameter 10 stud	
Brake size	420 x 180mm		420 x 180mm		420 x 180mm	
Wheel track	1800mm	5' 11"	1800mm	5' 11"	1800mm	5' 11"
Tyre size	445/65R22.5 Kargo radial		445/65R22.5 Kargo radial		445/65R22.5 Kargo radial	
O/all length	7730mm	25' 3"	8330mm	27' 4"	8330mm	27' 4"
O/all width	2455mm	8' 1"	2455mm	8' 1"	2455mm	8' 1"
O/all height	2450mm	8'	2450mm	8'	2650mm	8' 8"
Max tipped height	6550mm	21' 6"	7010mm	23'	7410mm	24' 4"
Unladen weight	Approx 5.2 Tonne		Approx 5.5 Tonne		Approx 5.7 Tonne	

Please note body dimensions can be amended to suit your particular needs.

**Tel : 01981 251558
Fax : 01981 251568**

**www.awtrailers.co.uk
sales@awtrailers.co.uk**

**AW Engineering (Hereford) Ltd.
Stoney Street, Madley
Hereford, HR2 9NQ**

	16 Tonne Ultima Bale		16 Tonne Ultima Industrial Dump	
Body length (internal)	7900mm	26'	4720mm	15' 6"
Body width (internal)	2500mm	8' 2"	2275mm	7' 6"
Body height (internal)	-	-	915mm	3'
Floor thickness	4mm		6mm	
Side thickness	-		6mm	
Cubic capacity	-	-	9.2m ³	320ft ³
Chassis	250 x 150 RHS		250 x 150 RHS	
Axle size	127mm diameter 10 stud		127mm diameter 10 stud	
Brake size	420 x 180mm		420 x 180mm	
Wheel track	1900mm	6' 3"	2000mm	6' 7"
Tyre size	445/65R22.5 Kargo radial		445/65R22.5 Kargo radial	
O/all length	9450mm	31'	6150mm	20' 2"
O/all width	2500mm	8' 2"	2455mm	8' 1"
O/all height	1230mm	4'	2295mm	7' 6"
Max tipped height	-	-	5950mm	19' 6"

AW Trailers. We're in it for the long haul.